

> Street Sweeper Geting: G1,G2,G3/traktor



03-06

Mählers' towed street sweepers are the first choice of professionals for their areas of application. With their maneuverability and ease of use, they are popular with property managers who have to deal with narrow courtyards and sidewalks as well as public squares and other large areas. The basic design with a direct intake was

developed with quality, function and capacity in mind. Our sweepers have no lift, which results in better operating economy. Dust is efficiently kept down with watering systems custom-designed for each model. Three advanced machines – all easy to use.

Technical data:	G1	G2	G3
Length incl. towbar/mm	3000	3900	4300
Length/mm	2400	3050	3400
Width/mm	1400	1650	1750
Height/mm	1110	1450	1750
Sweeping path, min-max/mm	1600-1900	1900-2200	1900-2600
Hopper capacity/liters	700	1500	2000
Fill capacity/liters	350	800	1500
Dumping height/mm	1500	1800	2000
Water tank/liters	200	500	1000
Frame control: r/l/mm/accessory	350	350	700
Compactor/accessory	-	-	Yes
RPM control/side brushes	-	Yes	Yes
Hydraulic brakes	-	Yes	Yes
Operating lights	-	Yes	Yes
Empty weight/kg	890	1300	2000
Total weight/kg	1550	2800	4900
Appropriate tow vehicle/min. hp (DIN)	20	40	60

Mähler & Söner AB, Mjölby: +46 (0)142-185 80
 Jokkmokk: +46 (0) 971 - 126 33
 Rossön: +46 (0) 624 - 203 50
www.mahlers.se